

This product has suited the following standards.

Strength performance regarding "Standard for Safety belt" by Ministry of Health, Labor and Welfare of Japan (No.38, 2002)
 "Safety belt structure guideline" by National Institute of Industrial Safety of Japan (NIIS-TR-No.35,1999)




The photograph is ST#551-SK-H. (ST#551-SK with ST#558-H)


ST#551-SK


- Belt** Polyester belt (W:47mm)
- Waist belt** Nylon belt (W:50mm)
- Buckle** Light weight type
- Total weight** 1,135g
- Belt color** ● ●

Lanyard for full body harness

ST#558-H 
 "Super lanyard" webbing
 + 508-50B hook

ST#558-SQ 
 Nylon webbing + Shock Absorber
 + 508-50B hook

ST#558-S 
 Aramid webbing with retractor
 + Shock Absorber + 508-50B hook

ST#558-HW 
 "Super lanyard" webbing
 + 508-50B hook + ST#508-M hook
 (It uses it for the second lanyard.)



- ST#551-N**
With out
Waist belt model
- ST#551-OT**
With waist belt &
Quick release buckle
- ST#551-SK-HW**
With waist belt
& Light weight buckle
2 lanyard model
(ST#558-H & HW)

Safety belt & Full body harness Accessories

ST#540"Self lock"retractor



| Model | Length |
|-----------|--------|
| ST#540-7 | 7m |
| ST#540-10 | 10m |
| ST#540-17 | 17m |
| ST#540-25 | 25m |
| ST#540-30 | 30m |
| ST#540-35 | 35m |



ST#598
"Hook holster"

Hook hanger

ST#586-P




ST#506-HC



"Insert bolt hanger"

ST#596

It corresponds
to 1/2 and 3/8
inch insert bolts.



ST#596-3



It corresponds
to 3/8 inch
insert bolts.

